

Seattle Boom Lift License

Seattle Boom Lift License - Just completely qualified individuals should operate an aerial boom lift. Qualification can be obtained through a combination of classroom sessions and practical training with the particular type of aerial lift that will be used on the job. A License is needed for anyone who operates or works on an aerial boom lift.

Various kinds of vehicle-mounted aerial devices include extensible boom platforms, aerial ladders, vertical towers, articulating boom platforms, and whichever combination of these kinds.

There are several basic safety regulations that apply to all boom lifts. Worker safety whilst in the basket is a top priority. Workers must wear a body harness and lanyard connected to the basket or boom. Never tie off to an adjacent pole, structure, or equipment. Staff should stand on the basket floor, and never sit or climb on the edge of the basket. The load restrictions of the manufacturer should be adhered to.

Lift operators need to be certified to operate an aerial lift. The manufacturer's guidebook should be kept in the lift and the operator should know all aspects of that specific unit. Operators are responsible for making certain that safety measures are followed in operating the lift. Testing lift controls everyday must be carried out. Set brakes and position outriggers (if they are utilized) on a stable surface or on pads. When working on a slope, utilize wheel chocks.

Never move an aerial lift truck with an elevated boom while workers are inside the basket. Articulating boom and extensible boom platforms made use of as employees carriers must have accessible, plainly marked, upper controls. Except in emergency situations, lower controls should not be utilized to override upper controls unless permission has been given by the person within the lift.

While working from an aerial lift, do not wear pole or tree climbers.

Do not alter the insulated part of the aerial lift.

Do inspect the booms to make sure that it is properly cradled and the outriggers are in the stowed position prior to moving.

When operating a boom lift next to power lines, ensure the lines are di-electrically tested based on local rules.